

Series E24 Normally Open Explosion Proof Solenoid Valve



*Max Oper Press Diff.		Orifice Size		CV Factor		CONDUIT HOUSING (1/2" NPT)	
AC	DC					1/8 NPT Ports	1/4 NPT Ports
400	400	1/32	1/32	.024	.024	E24GG7XCCM	E24GG9ZCCM
150 (225)	150	3/64	1/16	.052	.095	E24HJ7XCCM	E24HJ9ZCCM
100 (150)	100	1/16	1/16	.095	.095	E24JJ7XCCM	E24JJ9ZCCM
100 (125)	100	1/16	1/8	.095	.214	E24JN7XCCM	E24JN9ZCCM
75 (90)	75	3/32	1/8	.156	.214	E24KN7XCCM	E24KN9ZCCM

Series E25 Directional Control Explosion Proof Solenoid Valve



*Max Oper Press Diff.		Orifice Size		CV Factor		CONDUIT HOUSING (1/2" NPT)	
AC	DC					1/8 NPT Ports	1/4 NPT Ports
500	500	1/32	1/32	.024	.024	E25GG7XCCM	E25GG9ZCCM
235 (400)	235 (300)	3/64	3/64	.052	.052	E25HH7XCCM	E25HH9ZCCM
200 (225)	200 (200)	1/16	3/64	.095	.052	E25JH7XCCM	E25JH9ZCCM
150 (225)	150 (200)	1/16	1/16	.095	.095	E25JJ7XCCM	E25JJ9ZCCM
100 (150)	100 (125)	3/32	3/32	.156	.156	E25KK7XCCM	E25KK9ZCCM
100 (125)	100	1/8	3/32	.214	.156	E25NK7XCCM	E25NK9ZCCM